



US 20170162808A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2017/0162808 A1
(43) Pub. Date: Jun. 8, 2017

(54) PHOTOELECTRIC CONVERSION DEVICE

(71) Applicant: SUMITOMO CHEMICAL COMPANY, LIMITED, Tokyo (JP)

(72) Inventor: Yasunori UETANI, Tsukuba-shi (JP)

(73) Assignee: SUMITOMO CHEMICAL COMPANY, LIMITED, Tokyo (JP)

(21) Appl. No.: 15/325,815

(22) PCT Filed: Jun. 30, 2015

(86) PCT No.: PCT/JP2015/068756

§ 371 (c)(1),

(2) Date: Jan. 12, 2017

(30) Foreign Application Priority Data

Jul. 14, 2014 (JP) 2014-143986

Publication Classification

(51) Int. Cl.

H01L 51/42 (2006.01)

H01L 51/00 (2006.01)

C08G 61/12 (2006.01)

H01L 27/30 (2006.01)

H01L 51/44 (2006.01)

(52) U.S. Cl.
CPC H01L 51/4246 (2013.01); H01L 27/302 (2013.01); H01L 51/442 (2013.01); H01L 51/448 (2013.01); C08G 61/126 (2013.01); H01L 51/0043 (2013.01); H01L 51/0036 (2013.01); H01L 51/0035 (2013.01); C08G 2261/91 (2013.01); C08G 2261/3246 (2013.01); C08G 2261/3247 (2013.01); C08G 2261/124 (2013.01); C08G 2261/228 (2013.01); C08G 2261/1412 (2013.01); C08G 2261/3243 (2013.01)

(57)

ABSTRACT

A photoelectric conversion device comprising a layer A having a hue value of h_1 in the L*C*h color system calculated from the transmittance spectrum and a layer B having a hue value of h_2 in the L*C*h color system calculated from the transmittance spectrum, wherein the above-described h_1 and the above-described h_2 satisfy $h_1+100 \leq h_2 \leq h_1+260$.